



IC4. CARPET CLEANING

BEST MANAGEMENT PRACTICES (BMP)

A BMP is a technique, measure, or structural control that is used for a given set of conditions to improve the quality of the stormwater runoff in a cost-effective manner.¹ The minimum required BMPs for this activity are outlined in the box to the right. Implementation of pollution prevention/good housekeeping measures may reduce or eliminate the need to implement other more costly or complicated procedures. Proper employee training is key to the success of BMP implementation.

The BMPs outlined in this fact sheet target the following pollutants:

TARGETED CONSTITUENTS	
<input checked="" type="checkbox"/>	Sediment
	Nutrients
	Floatable Materials
	Metals
	Bacteria
	Oil and Grease
<input checked="" type="checkbox"/>	Organics and Toxicants
	Pesticides
	Oxygen Demanding

MINIMUM BEST MANAGEMENT PRACTICES

Pollution Prevention/Good Housekeeping

- Discharge wash water to sink, toilet, or other drain connected to the sanitary sewer system.
- Stencil storm drains.

Training

- Train employees on these BMPs, stormwater discharge prohibitions, and wastewater discharge requirements.
- Provide ongoing employee training in pollution prevention.

Provided below are specific procedures associated with each of the minimum BMPs along with procedures for additional BMPs that should be considered if this activity takes place at a facility located near a sensitive waterbody. In order to meet the requirements for medium- and high-priority facilities, the owners/operators must select, install, and maintain appropriate BMPs on site. Since the selection of the appropriate BMPs is a site-specific process, the types and numbers of additional BMPs will vary for each facility.

1. Discharge wash water to sink, toilet, or other drain connected to the sanitary sewer system.

- Never discharge wash water to a street, gutter, parking lot, or storm drain. Either:
 - empty the spent cleaning fluid tank into a utility sink or other indoor sewer connection at the service provider's home base
 - or
 - arrange with the customer to discharge into a toilet or utility sink on his premises.
- Check the local wastewater authority's requirements for discharge.
- Filter wash water before discharging to the sanitary sewer to avoid clogging pipes. Dispose of filtered material in the garbage, provided the carpet was not contaminated with hazardous materials.
- These guidelines apply event to cleaning products labels "nontoxic" and "biodegradable."

¹ EPA Preliminary Data Summary of Urban Stormwater Best Management Practices

TRAINING

- 1. Train employees on these BMPs, stormwater discharge prohibitions, and wastewater discharge requirements.**
- 2. Train employees on proper spill containment and clean-up.**
 - Establish training that provides employees with the proper tools and knowledge to immediately begin cleaning up a spill.
 - Ensure that employees are familiar with the site's spill control plan and/or proper spill clean-up procedures.
 - BMP IC17 discusses Spill Prevention and Control in detail.
- 3. Establish a regular training schedule, train all new employees, and conduct annual refresher training.**
- 4. Use a training log or similar method to document training.**

STENCIL STORM DRAINS

Storm drain system signs act as highly visible source controls that are typically stenciled directly adjacent to storm drain inlets. Stencils should read *NO DUMPING DRAINS TO OCEAN*.

REFERENCES

California Storm Water Best Management Practice Handbook. Industrial and Commercial. 2003.

www.cabmphandbooks.com

Water Quality Guidelines for Carpet Cleaning Activities. Orange County Stormwater Program. Prepared by Watershed & Coastal Resources Division. January 2002.

http://www.ocwatersheds.com/PublicEducation/pe_brochures_carpet.asp

For additional information, contact:

City of Mission Viejo
Department of Public Works
200 Civic Center Drive
Mission Viejo, California 92691
949.470.3056
www.cityofmissionviejo.org